

TPS-6X

Isys™ 5.7" Wireless Touchpanel

The Isys TPS-6X Wireless Touchpanel delivers high-end style and performance in a very versatile, ergonomic design. With its sleek and innovative desktop docking station, the TPS-6X goes effortlessly from wired tabletop use to fully wireless handheld operation.

Compact and portable, the TPS-6X does away with piles of remotes and cryptic control panels, affording true "one-touch" control over a broad range of complex devices and systems. Featuring a bright, beautiful, high-contrast color touchscreen, and a smart array of backlit tactile pushbuttons^[1], the TPS-6X offers an ideal user-interface for controlling home theater and multimedia presentation, and a host of other uses.

Isys™ Color Touchscreen

The TPS-6X provides a wide open canvas for the creation of custom control screens tailored to each unique application. Its brilliant 5.7" active-matrix display and powerful Isys engine combine to produce stunning 16-bit color graphics with extreme versatility and lightning-fast performance. Dynamic graphics and text capability enable the display of all kinds of useful data and alluring eye candy—from audio settings, TV channels, and lighting levels—to changing icons, photos, and logos—to digital media playlists complete with album cover art.

Crestron exclusive DNav and Synapse™ technologies enable system programmers to produce amazing graphics faster and easier using advanced dynamic control menus and 3D effects. Additional capabilities like animations, multimode objects, PNG translucency, and full-motion video^[2] enhance the palette for creating GUIs that are both eye-catching and easy to use.

Tactile Pushbuttons

In addition to its touchscreen, the TPS-6X features illuminated tactile pushbuttons for quick access to volume adjustment, channel selection, and on-screen menu navigation functions. Eight additional pushbuttons, elegantly trimmed by illuminated button dividers, flank the edges of the touchscreen to support additional programmable functions.

High-quality backlit laser-engraving lends a crisp, legible appearance to button text in both darkened and fully lit rooms^[1]. The pushbuttons come pre-engraved with labeling suited to a typical home theater or multimedia presentation application. If needed, customized engraving can be attained simply using Crestron Engraver software. A no-button front bezel is also included with the TPS-6X, which may be installed in place of the button bezel for a very clean appearance with no front panel pushbuttons.

Two additional "trigger" style buttons are positioned on top of the TPS-6X for easy control of the display brightness, sleep mode, and other programmable functions.

High Powered Wireless

The TPS-6X brings a new level of wireless versatility to the Isys family of touchpanels. With both 2-way RF and 1-way IR wireless capabilities built in, the TPS-6X offers a choice of wireless platforms to suit the environment.

Crestron high-power 2.4 GHz RF technology allows long range performance up to 200 feet indoors^[3] using the CEN-HPRFGW High Powered RF Gateway^[4]. For even greater coverage, the TPS-6X supports roaming amongst up to 8 CEN-HPRFGW gateways. A range of selectable RF channels and power levels helps to maximize performance for both small and large



facilities—from boardrooms, classrooms, and home theaters to auditoriums and convention centers. High-speed bidirectional communication supports true feedback with dynamic graphics and text, affording the capabilities of a wired Isys touchpanel in a fully wireless portable package.

Built-in IR capability affords a wireless alternative that's immune to extremely noisy RF environments, and suitable for sensitive applications where RF may not be permitted. An operational range of up to 50 feet line-of-sight is possible using a C2N-IRGW-1G or C2N-IRGW-F IR Gateway^[4], or CNXRMRD IR Receiver^[4].

TableTop Tilt Docking Station

Placing the touchpanel onto the TPS-6X-DS Docking Station^[5] converts it to a stylish tilt touchpanel, providing wired communications and video capability while charging the touchpanel's internal battery. Both wired Ethernet and Cresnet® connectivity are available, so when the touchpanel is placed on the docking station, it can switch automatically from RF wireless to fully-wired operation if either Ethernet or Cresnet is connected. Without a wired connection present, the touchpanel will continue to operate wirelessly while it charges.

The docking station features a tiltable docking port, allowing the touchpanel to be tilted at any angle up to 45 degrees for optimal viewing and operation when docked. The angle can be freely adjusted, or locked down at a fixed angle. Strong magnets help guide the touchpanel onto the docking port and hold it in place, and a finger-operated latch can be engaged at any time to secure the touchpanel to the docking station^[6]. The touchpanel can even be attached to the docking station semi-permanently using a provided locking pin for a sleek, full-time tabletop touchpanel solution^[6].

A single cable exits the rear of the docking station base, extending to a wall or surface mounted TPS-6X-IMCW Interface Module^[5]. The cable can also be repositioned to exit the bottom for a very clean, cordless appearance.

Full-Motion Video^[2]

When docked, the TPS-6X can display full-motion video, providing the ability to monitor a security camera, or preview a DVD or television channel, right on the touchscreen display. The video image is fully

TPS-6X Isys™ 5.7" Wireless Touchpanel

scalable for viewing in any sized window or full screen. The choice of balanced or unbalanced composite inputs allows compatibility with both conventional coaxial and Crestron Home® Balanced AV distribution systems.

> *Lightweight contoured design for wireless handheld use*

> *Also affords full-featured tabletop tilt touchpanel operation*

> *Elegant high gloss black or white, or matte black finishes*

> *Non-slip rubber grips on rear*

> *Illuminated buttons and engravable backlit text^[1]*

> *5.7" active matrix color touchscreen display*

> *16-bit Isys™ graphics | 640 x 480 resolution*

> *Dynamic graphics & text capability*

> *DNav dynamic menu objects*

> *Synapse Image Rendering Algorithm*

> *Displays full-motion video while docked*

> *High-power, high-speed 2.4 GHz RF wireless technology*

> *Up to 200 feet RF range indoors*

> *Supports roaming for extended RF coverage*

> *1-way IR wireless capability also built in*

> *Includes tabletop tilt docking station, interface module, and NiMH rechargeable battery pack*

> *Wired Ethernet, Cresnet, and Crestron Home CAT5 video connectivity*

> *No-button front bezel option included*

SPECIFICATIONS

Touchscreen Display

Display Type: TFT Active matrix color LCD

Size: 5.7 inch (14.48 cm) diagonal

Aspect Ratio: 4:3 VGA

Resolution: 640 x 480 pixels

Brightness: 350 nits (cd/m²)

Contrast: 400:1

Color Depth: 18-bit, 256k colors

Illumination: Backlit fluorescent

Viewing Angle: ±80° horizontal, +80°/-70° vertical

Touchscreen: Resistive membrane

Buttons & Switches

Sleep: (1) Programmable top-mounted pushbutton (left); normally initiates "Sleep" mode when docked, turns power on/off when undocked; also resets touchpanel if held for 5 seconds

Brightness: (1) Programmable top-mounted pushbutton (right), normally sets display brightness level

Hard Keys: (8) Optional programmable pushbuttons, engravable backlit text^[1,4] (default engraving included)

Up/Down: (2) Optional programmable "up/down" pushbuttons, backlit, engravable backlit text on bezel (default engraving included)

Thumbpad: (5) Optional programmable pushbuttons for 4-way directional navigation and "enter", backlit

Battery: (1) Rear panel recessed DIP switch, shuts off battery for long-term storage

LED Indicators

Battery: (1) Green LED, indicates battery condition and charging status when docked

Connectors

Docking Connector: (1) multi-pin connector;

Mates with the docking port on the **TPS-6X-DS** docking station^[5]

See the **TPS-6X-IMCW** interface module^[5] specification for other connectors

Processor

CPU: 32-bit Freescale ColdFire® Microprocessor

Memory

SDRAM: 32 MB

Flash: 32 MB

Maximum Project Size: 28 MB

Graphic Engine

Isys engine; 16-bit non-palette graphics; 65,536 colors; Synapse image rendering algorithm; multi-mode objects, DNav dynamic menu objects, dynamic graphics, PNG translucency, full-motion (60 fps) animation, color key video windowing

RF Wireless

RF Transceiver: 2-way RF, 2.4 GHz ISM Channels 11-26 (2400 to 2483.5 MHz), IEEE 802.15.4 compliant

Transmitting Power: 75 mW (Ch.11), 100 mW (Ch.12-23), 15 mW (Ch.24), 3.5 mW (Ch.25), 1 mW (Ch.26) @ High Setting; 1 mW (Ch.11-25), 0.5 mW (Ch.26) @ Low Setting

Range: 100 to 200 feet maximum indoor, 1000 feet outdoor, subject to site-specific conditions

Gateway: Requires a **CEN-HPRFGW** RF Gateway^[4]

Roaming: Supports roaming amongst up to 8 RF gateways

IR Wireless^[7]

IR Transmitter: 38 kHz, RC5 format

Range: 50 feet typical

Gateway: Requires a **C2N-IRGW-1G** or **C2N-IRGW-F** IR Gateway^[4], or

CNXRMIRD IR Receiver^[4]

Wired Communications^[2]

Ethernet: 10BaseT/100BaseTX, auto-switching, auto-negotiating, auto-discovery, full/half duplex, TCP/IP, UDP/IP, CIP, DHCP

Cresnet: Supports Cresnet slave mode

TPS-6X Isys™ 5.7" Wireless Touchpanel

Video^[2]

Signal Types: Composite

Formats: NTSC 480i or PAL 576i

Color Depth: 18-bit; 262,144 colors

Windowing: Single-window, deinterlaced and scalable up to full-screen

Audio

Internal transducer for keyclick sound

Battery

Internal Battery: NiMH, 4.8 Volt, 2000 mAh, model **TPS-6X-BTP**^[5]

Usage per Charge: ~2 hours continuous, 2 days under normal use with factory settings

Charging Time: ~2.5 hours (~2.5 to 3 hours when in use)

Power Requirements

Power Pack: 0.75 Amps @ 24 Volts DC;

100-240 Volts AC, 50/60 Hz power pack, model **PW-2407WU** included

Cresnet Power Usage: 18 Watts (0.75 Amps @ 24 Volts DC), includes **TPS-6X-IMCW** module^[5]

Note: May be powered by power pack or Cresnet network power, not both. All power connections are made via the TPS-6X-IMCW interface module^[5]

Environmental

Temperature: 32° to 112°F (0° to 45°C);

50° to 104°F (10° to 40°C) while charging

Humidity: 10% to 90% RH (non-condensing)

Heat Dissipation: 61 BTU/hour

Enclosure

Construction: Injection-molded plastic, non-slip grips/feet, integral docking station port

Front Bezels: Button and no-button bezels included; button bezel includes white translucent illuminated Up/Down and Thumbpad buttons and 8 hardkey buttons with illuminated dividers and default backlit text engraving, optional custom backlit text engraving sold separately^[1]

Dimensions

Height: 5.10 in (130 mm)

Width: 8.08 in (206 mm)

Depth: 1.57 in (40 mm)

Note: Combined height of the TPS-6X touchpanel docked on the TPS-6X-DS docking station is 6.21 in (158 mm) maximum.

Weight

1.59 lb (720 g)

Available Models

TPS-6X: Isys™ 5.7" Wireless Touchpanel, Gloss Black

TPS-6X-B-T: Isys™ 5.7" Wireless Touchpanel, Matte Black

TPS-6X-W-S: Isys™ 5.7" Wireless Touchpanel, Gloss White

TPS-6XNL: Isys™ 5.7" Wireless Touchpanel w/No-Lock DS, Gloss Black

TPS-6XNL-B-T: Isys™ 5.7" Wireless Touchpanel w/No-Lock DS, Matte Black

TPS-6XNL-W-S: Isys™ 5.7" Wireless Touchpanel w/No-Lock DS, Gloss White

Included Accessories

TPS-6X-BTP Replacement battery pack for TPS-6X

[Included Quantity for TPS-6X, TPS-6X-B-T, TPS-6X-W-S, TPS-6XNL, TPS-6XNL-B-T, TPS-6XNL-W-S: 1]

TPS-6X-DS Desktop Docking Station for TPS-6X, Gloss Black

[Included Quantity for TPS-6X: 1]

TPS-6X-DS-B-T Desktop Docking Station for TPS-6X-B-T, Matte Black

[Included Quantity for TPS-6X-B-T: 1]

TPS-6X-DS-W-S Desktop Docking Station for TPS-6X-W-S, Gloss White

[Included Quantity for TPS-6X-W-S: 1]

TPS-6XNL-DS Desktop Docking Station for TPS-6X, No-Lock, Gloss Black

[Included Quantity for TPS-6XNL: 1]

TPS-6XNL-DS-B-T Desktop Docking Station for TPS-6X-B-T, No-Lock, Matte Black

[Included Quantity for TPS-6XNL-B-T: 1]

TPS-6XNL-DS-W-S Desktop Docking Station for TPS-6X-W-S, No-Lock, Gloss White

[Included Quantity for TPS-6XNL-W-S: 1]

TPS-6X-IMCW Interface Module for TPS-6 and TPS-6X-DS

[Included Quantity for TPS-6X, TPS-6X-B-T, TPS-6X-W-S, TPS-6XNL, TPS-6XNL-B-T, TPS-6XNL-W-S: 1]

PW-2407WU Wall Mount Power Pack 24VDC, 0.75A, Universal

[Included Quantity for TPS-6X, TPS-6X-B-T, TPS-6X-W-S, TPS-6XNL, TPS-6XNL-B-T, TPS-6XNL-W-S: 1]

TPS-6X-FP_ENGRAVED Backlit Engravable Button Bezel Kit w/Custom Engraving, Gloss Black

[Included Quantity for TPS-6X, TPS-6XNL: 1]

TPS-6X-FP-NB No-Button Bezel Kit for TPS-6 & TPS-6X, Gloss Black

[Included Quantity for TPS-6X, TPS-6XNL: 1]

TPS-6X-FPB-T_ENGRAVED Backlit Engravable Button Bezel Kit w/Custom Engraving, Matte Black

[Included Quantity for TPS-6X-B-T, TPS-6XNL-B-T: 1]

TPS-6X-FPB-T-NB No-Button Bezel Kit for TPS-6-B-T & TPS-6X-B-T, Matte Black

[Included Quantity for TPS-6X-B-T, TPS-6XNL-B-T: 1]

TPS-6X-FPW-S_ENGRAVED Engravable Button Bezel Kit w/Custom Engraving, Gloss White

[Included Quantity for TPS-6X-W-S, TPS-6XNL-W-S: 1]

TPS-6X-FPW-S-NB No-Button Bezel Kit for TPS-6-W-S & TPS-6X-W-S, Gloss White

[Included Quantity for TPS-6X-W-S, TPS-6XNL-W-S: 1]

Available Accessories

TPS-6X-FP_ENGRAVED: Backlit Engravable Button Bezel Kit w/Custom Engraving, Gloss Black

TPS-6X-FP_BLANK: Backlit Engravable Button Bezel Kit (blank), Gloss Black

TPS-6X-FPB-T_ENGRAVED: Backlit Engravable Button Bezel Kit w/Custom Engraving, Matte Black

TPS-6X-FPB-T_BLANK: Backlit Engravable Button Bezel Kit (blank), Matte Black

TPS-6X-FPW-S_ENGRAVED: Engravable Button Bezel Kit w/Custom Engraving, Gloss White

TPS-6X-FPW-S_BLANK: Engravable Button Bezel Kit (blank), Gloss White

CEN-HPRFGW: High Powered RF Gateway

CENI-HPRFGW: High Powered RF Gateway - International Version, 230V

C2N-IRGW-1G: Wall Mount IR Gateway

C2N-IRGW-F: Flush Mount IR Gateway

CNXRMIRD: IR Receiver

TPS-6X-DS-C: Desktop Docking Station, Charging Only, Gloss Black

TPS-6X-DS-C-B-T: Desktop Docking Station, Charging Only, Matte Black

TPS-6X-DS-C-W-S: Desktop Docking Station, Charging Only, Gloss White

TPS-6XNL-DS-C: Desktop Docking Station, Charging Only, No-Lock, Gloss Black

TPS-6X Isys™ 5.7" Wireless Touchpanel

TPS-6XNL-DS-C-B-T: Desktop Docking Station, Charging Only, No-Lock, Matte Black

TPS-6XNL-DS-C-W-S: Desktop Docking Station, Charging Only, No-Lock, Gloss White

SMK-6X: Swivel Mount Kit

TPS-6X-DSW: Wall Mount Docking Station, Gloss Black

TPS-6X-DSW-B-T: Wall Mount Docking Station, Matte Black

TPS-6X-DSW-W-S: Wall Mount Docking Station, Gloss White

CRESNET-NP-TL-B250: Cresnet® Control Cable, non-plenum, teal, 250 ft box

CRESNET-NP-TL-B500: Cresnet® Control Cable, non-plenum, teal, 500 ft box

CRESNET-NP-TL-SP500: Cresnet® Control Cable, non-plenum, teal, 500 ft spool

CRESNET-NP-TL-SP1000: Cresnet® Control Cable, non-plenum, teal, 1000 ft spool

CRESNET-NP-BK-B500: Cresnet® Control Cable, non-plenum, black, 500 ft box

CRESNET-NP-OR-B500: Cresnet® Control Cable, non-plenum, orange, 500 ft box

CRESNET-NP-YL-B500: Cresnet® Control Cable, non-plenum, yellow, 500 ft box

CRESNET-P-TL-SP500: Cresnet® Control Cable, plenum, teal, 500 ft spool

CRESNET-P-TL-SP1000: Cresnet® Control Cable, plenum, teal, 1000 ft spool

CRESNET-P-BK-SP500: Cresnet® Control Cable, plenum, black, 500 ft spool

CRESNET-P-OR-SP500: Cresnet® Control Cable, plenum, orange, 500 ft spool

CRESNET-P-YL-SP500: Cresnet® Control Cable, plenum, yellow, 500 ft spool

CRESNET-HP-NP-TL-SP500: Cresnet® "High-Power" Control Cable, non-plenum, teal, 500 ft spool

CRESNET-HP-NP-TL-SP1000: Cresnet® "High-Power" Control Cable, non-plenum, teal, 1000 ft spool

CRESCAT-NP-SP500: Crestron Home® CAT5 AV Cable, Single CAT5e & Cresnet, non-plenum, 500 ft spool

CRESCAT-D-NP-SP500: Crestron Home® CAT5 AV Cable, 2x CAT5e & Cresnet, non-plenum, 500 ft spool

CRESCAT-D-HP-NP-TL-SP500: Crestron Home® CAT5 AV Cable, 2x CAT5e & Cresnet "High-Power", non-plenum, teal, 500 ft spool

Notes:

1. Text engraving is not backlit on the white models.
2. Requires a wired connection via the docking station and interface module.
3. 100 to 200 feet indoor range, subject to site-specific conditions.
4. Item sold separately.
5. Item included, see individual product specifications for additional information.
6. Models with "No-Lock" docking stations omit the finger-operated latch and locking pin features.
7. When IR wireless is enabled, the RF transceiver is disabled, and wired communication is restricted to console functions only (i.e., programming and configuration).



TPS-6X Isys™ 5.7" Wireless Touchpanel

